



# Simplex Strainer– ST Series

Nothing is too large to build , 2” to 48” size available



## Simplex Strainer


Simplex pipeline strainers remove particles that may cause damage to the system, it means to protect system components such as flow meters, pumps, and spray nozzles.

The particulate matter is captured in the strainer basket.


Heat Jacketed version is also available

### Features

Cover Closure Choice



Bolting Type



Quick opening type

### Specification

Material  
Carbon Steel ,SS304, SS316

Connection Type  
ANSI, JIS and DIN

Pressure rating  
10 Bar

Size  
2” to 48” size

Pressure Rating  
150#, 300#, 600#, 900# and 1500#

Basket  
SS304 or SS316 material  
From 25-400 mesh, 2 -10 mm perforate



How to order

**Strainer Code**                      **ST- A- 150#- 25/ 3 – 020A**

Material

- A- SS304
- S – SS316
- C – Carbon Steel

Pressure rating

- 150#, 300#, 600#
- 900#, 1500#

Mesh Lining

- 25, 50, 80, 100,
- 200,300, 400,600,
- 800 micron

Perforate Plate

- 3 , 5, 8, 10 mm

Flange Size

- 010 – 1”
- 020 – 2”
- 030 – 3”
- 040 - 4” and so on

Asia Pacific Regional Office

**Universal Filtration Solutions Asia Pte Ltd**

81 Ubi Ave 4, UB-ONE #06-28, Singapore 408830