



Y Strainer – STY Series

1/4 ” to 30” size available



Y Strainer

Y strainer remove particles that may cause damage to the system, it means to protect system components such as flow meters, pumps, and spray nozzles.

The particulate matter is captured in the strainer screen.

Our Y Strainer is available in cast or fabricate to design to meet your requirement.

All fabricated strainers are design according to ASME standard

Features

Fabricate Y Strainer
Design accordance to ASME standard

Custom design possible

Specification

Material
Carbon Steel ,SS304, SS316

Connection Type
BSP, FNPT Thread
ANSI, JIS and DIN Flange

Pressure rating
10, 16, 25 Bar

Size
2” to 30” size

Screen
SS304 or SS316 material
From 25-400 mesh, 2 -10 mm perforate



How to order

Y Strainer Code STY- A- 150#- 25/ 3 – 020A

Material

- A- SS304
- S – SS316
- C – Carbon Steel

Pressure rating

- 150#, 300#, 600#
- 900#, 1500#

Mesh Lining

- 25, 50, 80, 100,
- 200,300, 400,600,
- 800 micron

Perforate Plate

- 3 , 5, 8, 10 mm

Flange Size

- 010 – 1”
- 020 – 2”
- 030 – 3”
- 040 - 4” and so on

Asia Pacific Regional Office

Universal Filtration Solutions Asia Pte Ltd

81 Ubi Ave 4, UB-ONE #06-28, Singapore 408830