



Mini Bag Filter Vessel PFN series

MINI BAG FILTER VESSEL

MINI BAG FILTRATION UNIT

SBR201912341

Contents

Mini Bag Filter Vessel How to order Page 1


Page 2

MINI BAG FILTER VESSEL

MINI BAG FILTRATION UNIT

Mini Bag Filter Vessel PFN series

MINI BAG FILTER VESSEL



Recommended Operating Pressure 6 Bar at 30 deg C. Max Operating Temperature at 100 deg C and Max Flow Rate – 2 m3/hr (Water).



Product Model

- PF1N8-6-010N for 1" NPT thread connection
- PF1N8-6-010B for 1" BSP thread connection

Design

- Best Sealing design suitable for critical filtration demands
- Precision casting head to reduce pressure loss
- Easy cleaning for your next job ASME Design



How To Order From US

Send us an inquiry, we will respond with a quote

Whether its for filter housing, filter bags, cartridges, or customisable solutions, we'll respond with a quotation for your needs. We ensure the highest quality finishes and consistency in our products. Email us your requirements and we'll get in touch.

Purchase order & agreement, and production

Once a purchase order is made and our payments terms are agreed to, we'll begin production of your order. Depending on the order, our lead time would vary between one week to four weeks. We'll keep you updated on the progress and status.

Completion, delivery, and sea freight

Once completed, we'll arrange a sea freight shipment to your specified location. We deliver internationally. Delivery by courier is also available. Clients can choose to arrange for self collection direct from our factories through a forwarder, if they would like to handle their own shipment.

For Inquiry contact us at Sales-Inquiry@universal-filtration.com



For Inquiry contact us at Sales-Inquiry@universal-filtration.com

Asia Pacific Regional Office
Universal Filtration Solutions Asia Pte Ltd
81 Ubi Ave 4, UB-ONE #06-28
Singapore 408830

TOP ENTRY BAG FILTER VESSEL

TOP ENTRY FILTRATION UNIT